

SPECIFICATION:

Heading:

Page 1, replace spelling error with - Non-provisional

Background of the Invention

1. Field of the Invention

Page 2, insert paragraph number - [01] This invention relates to the field of thermal ...

2. Description of the Prior Art

Page 2, insert paragraph number - [02] A search of the prior art reveals numerous ...

Page 2, insert paragraph number - [03] In 1824, Nicolas Leonard “Sadi” Carnot, a ...

Page 3, insert paragraph number - [04] The Rankine cycle itself is inherently ...

Page 3, insert paragraph number - [05] The latest attempts to improve upon the ...

Page 4, insert paragraph number - [06] There exists a class of heat engines known as ...

Page 4, replace with following new paragraph:

[07] One of the principal reasons for the resistance to these devices is that they involve extensive and therefore expensive redesigns of existing facilities; as a result they are not being widely used to rehabilitate older power plants. New facilities, currently under construction, are just now starting to incorporate some of these design elements, yet the larger opportunity is to retrofit the worldwide base of currently operating electrical power generating facilities. To do this, a design approach that accomplishes the following key points must be employed: the design must be environmentally friendly, the design must not require expensive changes to the “host” facility, the design must be reliable, and the design must produce an acceptable financial return. Such a design will meet with

success, to date, not a single example of the prior art has satisfied all of these requirements.

Brief Summary of the Invention

1. Overview

Page 5, replace with the following new paragraph:

[08] In accordance with the present invention a waste heat recycling thermal power plant ~~1000~~ comprises a multitude of interacting volatile working fluid(s) circuits that generate a thermal potential between itself and an employable external heat source, extracting useable heat from that heat source (to replace the heat converted to work mechanical energy or otherwise lost from the system), generating a super-ambient temperature heat source and a sub-ambient temperature heat sink, whose thermal potential is capable of providing a useable heat flow to fuel its incorporated heat engine, recycling collected system thermal losses and ~~most~~ much of the useable heat flow that is rejected by its incorporated heat engine to its super-ambient temperature heat source, and the resultant mechanical power output produced by its incorporated heat engine is employed to drive a mechanical load (e.g., gearbox, electrical generator, propeller shaft, etc.).

2. Objects & Advantages

Page 6, replace with the following new paragraph:

[09] Accordingly, several objects and advantages of the present invention are:

(a) to provide a thermal power plant which can capture and reuse ~~most~~ much of the waste heat that its own operation liberates;

- (b) to provide a thermal power plant which can extract useable heat from the environment;
- (c) to provide a thermal power plant which can extract useable heat from a “low-temperature” external heat source;
- (d) to provide a thermal power plant which can extract useable heat utilizing a small thermal potential;
- (e) to provide a thermal power plant, which can extract useable heat from the waste heat that is rejected by a “host” heat engine;
- (f) to provide a thermal power plant which can create a thermal potential between itself and an employable external heat source;
- (g) to provide a thermal power plant which having created a thermal potential between itself and an employable external heat source, can utilize the heat extracted from that external heat source to fuel its own operation;
- (h) to provide a thermal power plant which can concentrate the extracted heat to generate a super-ambient temperature heat source to ~~provide~~ supply a useable heat flow to its incorporated heat engine;
- (i) to provide a thermal power plant which can generate a sub-ambient pressure region sufficient to evaporate a portion of its liquid working fluid ~~liquid~~ flow at a sub-ambient temperature, thus creating a sub-ambient temperature heat sink for its incorporated heat engine;
- (j) to provide a thermal power plant which can supply a useable heat flow between its super-ambient temperature heat source and its sub-ambient temperature heat sink, sufficient to fuel its incorporated heat engine;

- (k) to provide a thermal power plant which can produce mechanical power in excess of its own operational requirements, sufficient to drive an electrical generator;
- (l) to provide a thermal power plant which can produce electrical power in excess of its own operational requirements, sufficient to provide electrical power to the local electrical power distribution grid;
- (m) to provide a thermal power plant which can improve the thermal efficiency of the “host” heat engine by lowering the temperature of the host’s heat sink;
- (n) to provide a thermal power plant which can improve the fuel efficiency of the “host” heat engine by allowing the “host” to operate at a lower power level while still meeting the electrical demand;
- (o) to provide a thermal power plant which can reduce the amount of chemical pollution released to the environment by allowing the “host” heat engine, or an allied heat engine located elsewhere on the electrical grid, to operate at a lower power level while still meeting the electrical demand; and
- (p) to provide a thermal power plant which can increase the output capacity of the “host” engine by adding its electrical output to that of the host’s electrical output.

Page 8, insert paragraph number - [10] Further objects and advantages are to provide: ...

Brief Description of the Drawings

Page 8, replace with the following new paragraph:

[11] Fig. 1A shows the main embodiment of the waste heat recycling thermal power plant 1000.

Page 8, replace with the following new paragraph:

[12] Fig. 1B shows the motive flow circuit 1100 of the main embodiment of the waste heat recycling thermal power plant 1000.

Page 8, replace with the following new paragraph:

[13] Fig. 1C shows the suction flow circuit 1200 of the main embodiment of the waste heat recycling thermal power plant 1000.

Page 8, replace with the following new paragraph:

[14] Fig. 1D shows the conjoined flow circuit 1300 of the main embodiment of the waste heat recycling thermal power plant 1000.

Page 8, replace with the following new paragraph:

[15] Fig. 1E shows the incorporated heat engine flow circuit 1400 of the main embodiment of the waste heat recycling thermal power plant 1000.

Page 8, replace with the following new paragraph:

[16] Fig. 1F shows the mechanical output device 1500 of the main embodiment of the waste heat recycling thermal power plant 1000.

Page 8, replace with the following new paragraph:

[17] Fig. 1G shows the heat recovery flow circuit 1600 of the main embodiment of the waste heat recycling thermal power plant 1000.

Page 9, replace with the following new paragraph:

[18] Fig. 1H shows the heat source flow circuit 1700 of the main embodiment of the waste heat recycling thermal power plant 1000.

Page 9, replace with the following new paragraph:

[19] Fig. 2A shows an alternative embodiment of the waste heat recycling thermal power plant **1000** (which details a different arrangement of components within the suction flow circuit).

Page 9, replace with the following new paragraph:

[20] Fig. 2B shows the suction flow circuit 1200 of an alternative embodiment of the waste heat recycling thermal power plant 1000.

Detailed Description

1. Main Embodiment – Physical Layout:

Page 9, replace with the following new paragraph:

[21] A waste heat recycling thermal power plant **1000** (Fig. 1A) consists primarily of two conjoined circuits, a motive flow circuit **1100** and a suction flow circuit **1200** of a volatile working fluid (the conjoined portions of motive flow circuit **1100** and suction flow circuit **1200** are identified as a conjoined flow circuit **1300**). Additionally, waste heat recycling thermal power plant **1000** includes an incorporated heat engine flow circuit **1400** connected to a mechanical output device **1500**, a heat recovery flow circuit **1600** (optional), a heat source flow circuit **1700**, and the subcomponents contained therein. These circuits and their subcomponents are described below; the interconnecting piping/ducting is described only where necessary to add clarity to the description.

Page 9, replace with the following new paragraph:

[22] Motive flow circuit **1100** (Fig. 1B) which originates at a cfd flow separation chamber **1340-30**, and successively flows through: a cfd motive flow

discharge **1340-40**, an mfc fluid transfer device **1120**, an mfc fluid filtering device **1130** (optional), an mfc fluid flow-regulating device **1140**, and discharges to conjoined flow circuit **1300** via a cfc sub-ambient pressure generating device **1320**, which completes the circuit.

Page 10, replace with the following new paragraph:

[23] Suction flow circuit **1200** (Fig. 1C) which originates at a cfd flow separation chamber **1340-30**, and successively flows through: a cfd suction flow discharge **1340-50**, an sfc fluid flow-regulating device **1220**, an sfc sfc-hsfc heat recycling heat transfer device **1230**, an sfc shrd-ssths fluid transfer device **1240** [which contains: an ssftd sfc working fluid inlet 1240-15, an ssftd shrd hsfc-sfc evaporative heat transfer device excess working fluid discharge inlet 1240-20, an ssftd cssd overpressure relief device working fluid discharge inlet 1240-30, an ssftd suction chamber 1240-35, and an ssftd ihfc-sfc evaporative heat transfer device working fluid discharge 1240-40], an sfc sub-ambient temperature heat sink **1250** [which contains: an ssths ihfc-sfc evaporative heat transfer device **1250-20**, an ssths liquid/vapor separation device **1250-30** (optional), and an ssths ihfc-sfc evaporative heat transfer device pressure-regulating device **1250-40**], an shrd hsfc-sfc evaporative heat transfer device ssths vapor supply device **1260**, an shrd hsfc-sfc evaporative heat transfer device liquid supply device **1270**, an sfc heat replenishment device **1280** [which contains: an shrd hsfc-sfc evaporative heat transfer device **1280-20**, an shrd liquid/vapor separation device **1280-30** (optional), an shrd hsfc-sfc super-heat heat transfer device **1280-40** (optional), and an shrd hsfc-sfc evaporative heat transfer device pressure-regulating device **1280-**

50], an sfc shrd-cspgd vapor transfer device 1290, an sfc shrd-ssftd excess tertiary liquid component transfer device 1295, and discharges to conjoined flow circuit 1300 via cfc sub-ambient pressure generating device 1320, which completes the circuit.

Page 11, replace with the following new paragraph:

[24] Conjoined flow circuit 1300 (Fig. 1D) which originates at a cspgd suction chamber 1320-40, and successively flows through: a cspgd conjoined flow discharge 1320-50, a cfc super-ambient temperature heat source 1330 [which contains: ~~a csths cfc ihefc heat transfer device 1330-20~~ [which contains: a ~~eehtd~~ csths super-heat heat transfer device 1330-20A (optional), a ~~eehtd~~ csths latent heat heat transfer boiler heating device 1330-20B, and a ~~eehtd~~ csths feed-heat heat transfer device 1330-20C (optional)]]], a cfc flow divider 1340 [which contains: a cfd conjoined flow ~~discharge~~ inlet 1340-20, a cfd flow separation chamber 1340-30, a cfd motive flow discharge 1340-40, or a cfd suction flow discharge 1340-50, ~~and~~ or a cfd fluid import/export device 1340-60], a cfc safety/service device 1350 [which contains: a cssd fluid thermal expansion device 1350-20, a cssd overpressure relief device 1350-30, and a cssd venting/servicing ~~port~~ device 1350-40], and discharges to motive flow circuit 1100 and suction flow circuit 1200 via cfc flow divider 1350, which completes the circuit.

Page 11, replace with the following new paragraph:

[25] Incorporated heat engine flow circuit 1400 (Fig. 1E) which originates at the inlet of an ihefc fluid transfer device 1420 (optional, not required if utilizing gravity-induced circulation), and successively flows through: an ihefc fluid

transfer device **1420** (optional), an ihefc super-ambient temperature heat source **1430** [which contains: ~~an isths efe ihefc heat transfer device 1430-20~~ [which contains: an ~~iehtd~~ isths feed-heat heat transfer device **1430-20A** (optional), an ~~iehtd~~ isths ihefc starting device **1430-20B** (optional), an ~~iehtd~~ isths latent-heat-heat transfer device boiler **1430-20C**, an ~~iehtd~~ isths liquid/vapor separation device **1430-20D** (optional), and an ~~iehtd~~ isths super-heat heat transfer device **1430-20E** (optional)]]], an ihefc vapor export device **1440** [which contains: an ived ihefc working fluid ~~discharge~~ inlet **1440-20**, an ived flow separation chamber **1440-30**, an ived overpressure relief device working fluid discharge **1440-40**, and an ived ipedlc working fluid discharge **1440-50**], an ihefc fluid flow-regulating device **1450**, an ihefc pressure expansion device **1460** (e.g., Rankine cycle vapor turbine), an ihefc sub-ambient temperature heat sink **1470** [which contains: an isths ihefc-sfc condensing heat transfer device **1470-20**, and an isths venting/servicing ~~port~~ device **1470-30**], and an ihefc fluid storage device **1415**, which completes the circuit.

Page 12, replace with the following new paragraph:

[26] An ihefc pressure expansion device lubrication circuit **1480** (optional) augments the incorporated heat engine flow circuit **1400**. Ihefc pressure expansion device lubrication circuit **1480** [optional, which contains: an ipedlc pressure-regulating device **1480-20**, an ipedlc vapor bearing device **1480-30**, and an ipedlc vapor flow-regulating device **1480-40**], bypasses around the ihefc fluid flow-regulating device **1450** and the ihefc pressure expansion device **1460**, via an ihefc vapor export device **1440** and an ihefc fluid return device **1490** [which

contains: an ifrd ihefc overpressure relief device working fluid ~~discharge~~ inlet **1490-20**, an ifrd ipedlc working fluid ~~discharge~~ inlet **1490-30**, an ifrd flow collecting chamber **1490-40**, and an ifrd isths ihefc-sfc condensing heat transfer device working fluid discharge **1490-50**]. In addition, an ihefc overpressure relief device **1485** is interposed between the ihefc vapor export device **1440** and the ihefc fluid return device **1490**.

Page 12, replace with the following new paragraph:

[27] Mechanical output device **1500** (Fig. 1F) is connected to incorporated heat engine flow circuit **1400**. Specifically, a mod driven mechanical device **1520** (e.g., gearbox, generator, propeller shaft, etc.) is connected to incorporated heat engine flow circuit **1400**'s ihefc pressure expansion device **1460** via a mod hermetic power coupling device **1510A** (omit if **1510B** is utilized) or a mod intermediate drive shaft with shaft sealing device **1510B** (omit if **1510A** is utilized), which completes the device.

Page 13, replace with the following new paragraph:

[28] Heat recovery flow circuit **1600** (optional, Fig. 1G) originates at the inlet of an hrfc ventilation motive device **1620**, and successively flows through: an hrfc ventilation motive device **1620**, an hrfc machinery space **1630** [which contains: an hms exposed surfaces **1630-20** (i.e., floor, walls, ceiling, equipment, piping, etc.), and an hms ~~space~~ overpressure relief device **1630-30** (discharges to the environment)], an hms cooling distribution device **1640** [optional, which includes: an hcdd working fluid ~~discharge~~ inlet **1640-20**, an hcdd distribution device **1640-30(x)** (one channel for each unit that requires cooling, "x" – the designation

changes for each unit), an hcdd cooled machinery unit **1640-40(x)** (“x” – the designation changes for each unit), and an hcdd cooling exhaust collection device **1640-50(x)** (“x” – designation changes for each unit)], ~~and~~ an hrfc heat recycling heat transfer device **1650** [which contains: an hhrhtd hrfc-hsfc heat recycling evaporative heat transfer device **1650-20**, and an hhrhtd hrfc-hsfc heat recycling condensing heat transfer device 1650-30, and an hhrhtd working fluid storage device 1650-40], which completes the circuit.

Page 13, replace with the following new paragraph:

[29] Heat source flow circuit **1700** (Fig. 1H) originates at the inlet of an hsfc fluid transfer device **1720** (optional, not required if utilizing gravity-induced circulation), and successively flows through: an hsfc fluid transfer device **1720** (optional), an hsfc fluid filtering device **1730** (optional), an hsfc fluid import/export device **1740**, an hsfc safety/service device **1750** [which contains: an hssm fluid thermal expansion device **1750-20**, an hssm overpressure relief device **1750-30**, and an hssm venting/servicing ~~port~~ device 1750-40], an hsfc heat source heat transfer device **1760**, an hsfc sfc-hsfc heat recycling heat transfer device **1770**, an hsfc hrfc-hsfc heat recycling ~~condensing~~ heat transfer device **1780**, an hsfc hsfc-sfc super-heat heat transfer device **1785** (optional), an hsfc hsfc-sfc evaporative heat transfer device **1790**, ~~and~~ an hsfc hsfc-sfc heat transfer device working fluid discharge temperature-regulating device **1795**, and an hsfc fluid return device 1715, which completes the circuit.

Page 14, insert paragraph number: [30] In addition, the circuits are constructed ...

Page 14, replace with the following new paragraph:

[31] Note: Other types of heat engines may be utilized in lieu of the example Rankine cycle vapor turbine unit described above (e.g., Stirling cycle engine, Seebeck cycle thermoelectric generator, etc.). Any heat engine, which is capable of employing the developed ~~thermal potential~~ temperature differential, may be interposed between cfc super-ambient temperature heat source 1330 and sfc sub-ambient temperature heat sink 1250. Depending upon the characteristics of the alternative heat engine, and the working fluid(s) utilized, configuration changes may be required (i.e., the routing of conjoined flow circuit 1300 through cfc super-ambient temperature heat source 1330 and suction flow circuit 1200 through sfc sub-ambient heat sink 1250 may need to be altered). In the forgoing, “ambient” refers to the conditions (in terms of absolute pressure and absolute temperature) at cfd flow separation chamber 1340-30, this reference point (a.k.a., an ambient conditions datum), depending upon the characteristics of the working fluid utilized in conjoined flow circuit 1300, could differ substantially from standard atmospheric conditions (i.e., 14.696 psia and 536.67 deg-R).

2. Main Embodiment – Operation

Page 15, replace with the following new paragraph:

[32] Every heat engine requires a source of heat to operate, typically it is a hydrocarbon-based fuel that is burned in order to release the energy stored in the substance’s inter-atomic chemical bonds. Depending upon the type of heat engine in question, it is normal for a large portion of the heat provided to such engines to be rejected to the environment (i.e., wasted, having performed no useful work).

This has been the state of the art since the first recorded example of a heat engine (in the first century AD, Hero of Alexandria, Egypt is said to have described his Aeolipile, a rudimentary steam turbine). To be sure, the state of the art has improved much over the intervening centuries, yet it remains an unbreakable rule (i.e., the Second Law of Thermodynamics) that all heat engines must reject heat in order to function, and waste heat recycling thermal power plant 1000 is no different in this regard. What is different is the proportion of heat rejected, and the methodology employed to conserve and reuse ~~most~~ much of the heat that is rejected in a typical heat engine.

Page 15, replace with the following new paragraph:

[33] Waste heat recycling thermal power plant 1000 (Fig. 1A) utilizes the interaction of motive flow circuit 1100, suction flow circuit 1200, conjoined flow circuit 1300, incorporated heat engine flow circuit 1400, mechanical output device 1500, heat recovery flow circuit 1600 (optional), and heat source flow circuit 1700 to capture and reuse ~~most~~ much of the waste heat that its own operation liberates. What follows is an examination of those interactions.

Page 15, replace with the following new paragraph:

[34] Heat source flow circuit 1700 (Fig. 1H) performs four essential functions in the operation of waste heat recycling thermal power plant 1000. First, it acquires ~~make-up~~ replenishment heat (i.e., replacing the heat that is converted to ~~work~~ mechanical energy or lost from the system) from the external heat source(s) (e.g., geothermal pool, solar collector, river, industrial process cooling water, etc.) via hsfc heat source heat transfer device 1760. Second, it receives recyclable heat

(i.e., heat that is wasted in a typical heat engine) from suction flow circuit 1200 via hsfc sfc-hsfc heat recycling heat transfer device 1770, and the heat recovery flow circuit 1600 (optional) via hfsc hrfc-hsfc heat recycling ~~eondensing~~ heat transfer device 1780 (optional). Third, it transports this heat (~~make-up~~ replenishment and recycled) to hsfc hfsc-sfc super-heat heat transfer device 1785 (optional) and hsfc hfsc-sfc evaporative heat transfer device 1790. Fourth, it provides “chilled” working fluid to hsfc heat source heat transfer device 1760.

Page 16, replace with the following new paragraph:

[35] The working fluid in heat source flow circuit 1700 is motivated by hsfc fluid transfer device 1720 (optional, not required if utilizing gravity-induced circulation), filtered by hsfc fluid filtering device 1730 (optional), and its flow is controlled by hsfc hfsc-sfc evaporative heat transfer device working fluid discharge temperature-regulating device 1795. This last element acts to increase the flow of hsfc working fluid 1710 in heat source flow circuit 1700 when hsfc hfsc-sfc evaporative heat transfer device 1790 discharge temperature decreases below the desired operating point, conversely it acts to decrease hsfc working fluid 1710 flow when the discharge temperature rises above the desired operating point (the desired operating point is user adjustable).

Page 16, replace with the following new paragraph:

[36] The remaining enumerated subcomponents of heat source flow circuit 1700 serve to protect the circuit itself from the hydraulic hazards associated with fluids in confined spaces (i.e., thermal expansion, and over-pressurization), as well as providing a way to add/remove working fluid to/from the circuit.

Page 17, replace with the following new paragraph:

[37] Heat recovery flow circuit **1600** (optional, Fig. 1G, omit if **1780** is not utilized) performs four essential functions in the operation of waste heat recycling thermal power plant **1000**. First, it receives recyclable heat from the heat liberating machinery units (e.g., gearbox, electric generator, electric motor(s), etc.) in hrfc machinery space **1630**. Second, it receives recyclable heat lost from hotter portions of the system [i.e., system heat lost to the surrounding environment by hms exposed surfaces **1630-20** (i.e., floor, walls, ceiling, equipment, piping, etc.), in this case the heat is “lost” to hrfc machinery space **1630**]. Note: heat lost by hrfc machinery space **1630** to the environment is non-recoverable; however, this loss may be minimized and/or partially offset by passive solar gain during the warmest portions of the year. Third, it transports this recycled heat to hsfc hrfc-hsfc heat recycling ~~condensing~~ heat transfer device **1780** (optional) via hrfc heat recycling heat transfer device **1650**. Fourth, it provides “chilled” working fluid to hcdd working fluid inlet **1640-20**.

Page 17, replace with the following new paragraph:

[38] The working fluid in heat recovery flow circuit **1600** is motivated by gravity-induced circulation; further, this circulation is augmented with hrfc ventilation motive device **1620**, and the flow of hrfc working fluid **1610** is controlled by the operation of the previous element. Hrfc ventilation device **1620** is operated at maximum output to increase the flow of hrfc working fluid **1610** in order to reduce the temperature in hrfc machinery space **1630**, minimum output is utilized to decrease the flow and increase the temperature to the desired level,

intermediate output levels are utilized to maintain the temperature at the desired level, once that temperature is attained (the desired operating point is user adjustable).

Page 18, replace with the following new paragraph:

[39] As heated gas tends to rise, hcdd working fluid inlet **1640-20** is located near the ceiling of hrhc machinery space **1630** from there hms working fluid **1640-10** is conducted via hms cooling distribution device **1640** [optional, ~~containing individual~~ which contains: an hcdd working fluid inlet 1640-20, hcdd distribution device **1640-30(x)** (one channel for each heat generating device, “x” – designation changes for each unit) conducts hms working fluid **1640-10** to hcdd cooled machinery unit **1640-40(x)** (“x” – designation changes for each unit) where it receives recyclable heat liberated by the operation of the cooled machinery unit, next hcdd machinery cooling exhaust collection device **1640-50(x)** (“x” – designation changes for each unit) conducts the heated hms working fluid **1640-10** via chimney effect to hrhc heat recycling heat transfer device **1650**]. The collected heat conducted to hrhc heat recycling device **1650** is transported to hsfc hrhc-hsfc heat recycling ~~condensing~~ heat transfer device **1780** (optional) via hhrhtd hrhc-hsfc heat recycling evaporative heat transfer device 1650-20, and an hhrhtd hrhc-hsfc heat recycling condensing heat transfer device 1650-30. Note: were a single operating point possible, this interconnection could be achieved more efficiently with a liquid-to-liquid heat transfer device; however, that type of operating environment is unlikely, and this evaporative/condensing interface provides a self-adjusting heat transfer device (i.e., the evaporative temperature

will rise/fall on its own until the rate of evaporation is equal to the rate of condensation, and a new heat transfer equilibrium is established).

Page 18, replace with the following new paragraph:

[40] In addition, hrfc machinery space **1630** is protected from over-pressurization damage by hms overpressure relief device **1630-30** (discharges to the environment), such damage is possible in the event of a catastrophic loss of working fluid containment and the resultant flashing of the working fluid to vapor, although the working fluid temperatures and pressures envisioned make this an extremely remote possibility.

Page 19, replace with the following new paragraph:

[41] Suction flow circuit **1200** (Fig. 1C) performs seven essential functions in the operation of waste heat recycling thermal power plant **1000**. First, it provides recyclable heat to heat source flow circuit **1700** via sfc sfc-hsfc heat recycling heat transfer device **1230**. Second, it utilizes residual sfc working fluid **1210** pressure to operate sfc shrd-ssths fluid transfer device **1240**, this element draws excess working fluid from shrd ~~shrd-hsfc~~ hsfc-sfc evaporative heat transfer device **1280-20** and along with sfc working fluid **1210** supplied via sfc sfc-hsfc heat recycling heat transfer device 1230 combines to provide vigorous circulation within the heat transfer passages of sfc sub-ambient temperature heat sink **1250**, and sfc heat replenishment device **1280**. Third, it receives recyclable heat (i.e., waste heat in a typical heat engine) from sfc sub-ambient temperature heat sink **1250**, this occurs specifically in ssths ihfc-sfc evaporative heat transfer device **1250-20**, where ~~most~~ much of ssths working fluid **1250-10** admitted is converted

to vapor. The portion of ssths working fluid **1250-10** that remains in liquid form is transported to sfc heat replenishment device **1280** via shrd hsfc-sfc evaporative heat transfer device ssths liquid supply device **1270**. The portion of ssths working fluid **1250-10** that is converted to vapor is transported to sfc heat replenishment device **1280** via shrd hsfc-sfc evaporative heat transfer device ssths vapor supply device **1260**, where it combines with the vapor formed in shrd hsfc-sfc evaporative heat transfer device **1280-20**, then through ssths liquid/vapor separation device **1250-30** (optional), ssths ihfc-sfc evaporative heat transfer device pressure-regulating device **1250-40**, and shrd hsfc-sfc evaporative heat transfer device ssths vapor supply device **1260**. Fourth, it receives make-up replenishment heat (i.e., replacing the heat converted to ~~work~~ mechanical energy or lost from the system) from heat source flow circuit **1700** via shrd hsfc-sfc evaporative heat transfer device **1280-20** and shrd hsfc-sfc super-heat heat transfer device **1280-40** (optional). Fifth, it transports ~~this~~ super-heated vapor to cfc sub-ambient pressure generating device **1320** via shrd liquid/vapor separation device **1280-30** (optional), shrd hsfc-sfc super-heat heat transfer device **1280-40** (optional), ~~and~~ shrd hsfc-sfc evaporative heat transfer device pressure-regulating device **1280-50**, and sfc shrd-cspgd vapor transfer device **1290**. Sixth, it provides the heat (i.e., latent heat of vaporization and super-heat contained within the super-heated vapor) required to increase the temperature of mfc working fluid **1110** to that observed at the discharge of cfc sub-ambient pressure generating device **1320**. Seventh, it provides working fluid to conjoined flow circuit **1300**.

Page 20, replace with the following new paragraph:

[42] Sfc working fluid ~~1310~~ 1210 flow is motivated by the pressure differential between cfd flow separation chamber ~~1340-30~~ and cspgd suction chamber ~~1320-40~~, and its flow is controlled by sfc fluid flow-regulating device ~~1220~~. Note: by producing a ~~low-pressure~~ region of sub-ambient pressure, cfc sub-ambient pressure generating device ~~1320~~ enables the pressure-regulating devices (~~1250-40~~ & ~~1280-50~~) to regulate the pressure of their respective evaporative heat transfer devices (~~1250-20~~ & ~~1280-20~~) by controlling the flow of working fluid vapor flow that exits their respective evaporative heat transfer device. This has an added benefit to the operation of waste heat recycling thermal power plant ~~1000~~; precision regulation of these evaporating pressures also produces precise control of the temperatures within the respective evaporative heat transfer device (~~1250-20~~ & ~~1280-20~~).

Page 21, replace with the following new paragraph:

[43] Motive flow circuit ~~1100~~ (Fig. 1B) performs four essential functions in the operation of waste heat recycling thermal power plant ~~1000~~. First, it produces the pressure differential that is responsible for motivating all working fluid flow in motive flow circuit ~~1100~~, suction flow circuit ~~1200~~, and conjoined flow circuit ~~1300~~. Second, it filters (if so configured) all the working fluids in those same circuits. Third, it provides the high-pressure working fluid to cfc sub-ambient pressure generating device ~~1320~~ that is required to generate a ~~low-pressure~~ region of sub-ambient pressure in cspgd suction chamber ~~1320-40~~. Fourth, it provides working fluid to conjoined flow circuit ~~1300~~.

Page 21, replace with the following new paragraph:

[44] Mfc working fluid 1110 is motivated by mfc fluid transfer device 1120, ~~and~~ is filtered by mfc fluid filtering device 1130 (optional), and its flow is controlled by mfc fluid flow-regulating device 1140. The previous element acts to decrease mfc working fluid 1110 flow, when the flow exceeds the desired operating point, and conversely it acts to increase the flow, when ~~it~~ the flow is below the desired operating point (the desired operating point is user adjustable).

Page 21, replace with the following new paragraph:

[45] Conjoined flow circuit 1300 (Fig. 1D) performs four essential functions in the operation of waste heat recycling thermal power plant 1000. First, it receives high-pressure liquid from motive flow circuit 1100 and super-heated vapor from suction flow circuit 1200, and combines these flows to produce the high temperature liquid working fluid ~~liquid~~ flow discharged from cfc sub-ambient pressure generating device 1320. Second, it transports this thermal energy-rich liquid working fluid ~~liquid~~ flow to cfc super-ambient temperature heat source 1330 where it ~~gives up~~ supplies heat to ihfc super-ambient temperature heat source 1430. Third, it provides working fluid to motive flow circuit 1100 and suction flow circuit 1200. Fourth, via cssd thermal expansion device 1350-20 it is possible to adjust the “ambient” pressure experienced at cfd flow separation chamber 1340-30.

Page 22, replace with the following new paragraph:

[46] Cfc working fluid 1310 flow is motivated by the pressure differential between ~~cfc sub-ambient pressure generating device~~ cspgd conjoined flow

discharge 1320-50 discharge and cfd flow separation chamber 1340-30, and is controlled by the resistance to flow inherent in the same circuit (i.e., depending upon configuration, multiple indirect heat transfer devices impede the flow of the working fluid). Note: the pressure differential generated between 1320-50 & 1340-30 will rise/fall on its own until the rate at which working fluid leaves the conjoined flow circuit 1300 is equal to the rate at which working fluid enters the same circuit, thus establishing a new mass transfer equilibrium.

Page 22, replace with the following new paragraph:

[47] Ccssd overpressure relief device 1350-30 is interposed between cfd flow separation chamber 1340-30 and ssftd ccssd overpressure relief device working fluid inlet 1240-30, in the event of an overpressure condition this element would allow excess working fluid to be routed to ssths ihfc-sfc evaporative heat transfer device 1250-20, which has a surge capacity. Ccssd venting/servicing port device 1350-40 allows for ~~adding or removing~~ adding/removing working fluid to/from conjoined flow circuit 1300.

Page 22, replace with the following new paragraph:

[48] Incorporated heat engine flow circuit 1400 (Fig. 1E) performs six essential functions in the operation of waste heat recycling thermal power plant 1000. First, it receives heat from conjoined flow circuit 1300 via ihfc super-ambient temperature heat source 1430. Second, it transports this heat to ihfc pressure expansion device 1460 via ihfc fluid flow-regulating device 1450. Third, it produces mechanical power by pressure expanding ihfc working fluid 1410 in ihfc pressure expansion device 1460 (e.g., Rankine cycle vapor turbine). Fourth,

it rejects recyclable heat to suction flow circuit **1200** via ihefc sub-ambient temperature heat sink **1470**. Fifth, it provides a hermetic circuit to lubricate ihefc pressure expansion device **1460** via ihefc pressure expansion device lubricating circuit **1480** (optional). Sixth, it provides working fluid to ihefc super-ambient heat source **1430** [this function can be accomplished utilizing gravity-induced circulation, augmented with or supplanted by, ihefc fluid transfer device **1420** (optional)].

Page 23, replace with the following new paragraph:

[49] The remaining enumerated subcomponents of incorporated heat engine flow circuit **1400** serve to protect the circuit itself from the hydraulic hazards associated with fluids in confined spaces (i.e., thermal expansion, and over-pressurization), as well as providing a device to add/remove working fluid to/from the circuit.

Page 23, replace with the following new paragraph:

[50] Mechanical output device **1500** (Fig. 1F) performs four essential functions in the operation of waste heat recycling thermal power plant **1000**. First, it receives the mechanical power produced by ihefc pressure expansion device **1460**. Second, it transmits this mechanical power to hrfc machinery space **1630** via mod hermetic power coupling **1510A** or mod intermediate drive shaft with shaft sealing device **1510B**. Third, it provides mechanical power to mod driven mechanical output device **1520** (e.g., gearbox, generator, propeller shaft, etc.). Fourth, it provides recyclable heat to heat recovery flow circuit **1600** via hrfc heat recycling heat transfer device **1650**.

Page 23, replace with the following new paragraph:

[51] To review, the operation of waste heat recycling thermal power plant 1000 (Fig. 1A), requires heat source flow circuit 1700 to acquire and transport replenishment heat in sufficient quantity to replace all of the heat that is converted to ~~work~~ mechanical energy or lost from the system. This heat is then transferred to suction flow circuit 1200 where it completes the evaporation of sfc working fluid 1210 flow, and super-heats the entire shrd hsfc-sfc evaporative heat transfer device pressure-regulating device 1280-50 inlet flow (i.e., all of the liquid working fluid provided to suction flow circuit 1200 from conjoined flow circuit 1300 is returned to conjoined flow circuit 1300 from suction flow circuit 1200 in the form of super-heated vapor). This super-heated vapor then combines with liquid from motive flow circuit 1100 in cfc sub-ambient pressure generating device 1320 to produce a thermal energy-rich liquid working fluid ~~liquid~~ flow which is provided to cfc super-ambient temperature heat source 1330. This heat is then ~~provided~~ supplied to ihfc flow circuit 1400 where a portion of it is converted to mechanical power by ihfc pressure expansion device 1460. This mechanical power is then transmitted via mechanical output device 1500 to mod driven mechanical device 1520 (e.g., gearbox, generator, propeller shaft, etc.) to drive a mechanical load. Wherever feasible, waste heat recycling thermal power plant 1000, captures and reuses ~~significant~~ substantial portions of the waste heat that its own operation liberates, in particular the heat rejected to sfc sub-ambient temperature heat sink 1250 by incorporated heat engine flow circuit 1400, thus lowering its net energy utilization per unit of mechanical power produced.

3. Alternative Embodiments - Physical Layout & Operation

Page 24, insert paragraph number - [52] The basic embodiment of the waste heat ...

Page 25, replace with the following new paragraph:

[53] One alternative embodiment of the waste heat recycling thermal power plant **1000** utilizes a reconfigured suction flow circuit (Fig. 2A). This approach combines most of the functions that are performed by the sfc sub-ambient temperature heat sink **1250** and the sfc heat replenishment device **1280** of the main embodiment (Fig. 1C) into a single device (Fig. 2B). Further, it eliminates one evaporation process and the need for a device to control that process' evaporation pressure. The operation of the alternative embodiment is also similar to that of the main embodiment; however, its reconfigured suction flow circuit **1200** can produce a colder heat sink temperature than that of the main embodiment. This alternative embodiment has much to recommend its adoption over that of the main embodiment, ~~but at this time, we have more experience with and understanding of the main embodiment.~~

Page 25, replace with the following new paragraph:

[54] Other alternative embodiments involve: rerouting the flow of the ihfc fluid flow-regulating device **1450** discharge to acquire additional super-heat by cooling the mod driven mechanical device **1520**, or rerouting the mfc fluid flow-regulating device **1140** discharge to acquire additional sensible heat by cooling the mod driven mechanical device **1520**, and still others involve various methods for evaporating the working fluid and/or the use of various combinations of working fluids.

4. Conclusion, Ramifications, and Scope

Page 25, replace with the following new paragraph:

[55] Accordingly, the reader will see that the waste heat recycling thermal power plant ~~1000~~ of this invention can be used to convert the heat contained in a thermal reservoir or a thermal stream to mechanical power, and thereby drive a mechanical load. In addition, the waste heat recycling that occurs within the invention itself enables the waste heat recycling thermal power plant ~~1000~~ to ~~operate~~ produce useable mechanical power at “high” net ~~thermal operating~~ efficiencies, even while extracting replenishment heat from “low-temperature” external heat sources. Furthermore, the waste heat recycling thermal power plant ~~1000~~ has these additional advantages in that

- * it permits the production of mechanical power without burning hydrocarbon-based fuel, thus eliminating the attendant release of “greenhouse” gases;
- * it permits the production of mechanical power with minimal modifications and/or adaptation expenses to a “host” facility;
- * it permits the production of mechanical power reliably, through its utilization of robust sub-components;
- * it permits the production of mechanical power without the need to purchase additional fuel, thus improving the fuel efficiency of the “host” facility;
- * it permits the production of mechanical power by extracting replenishment heat directly from the environment.

Page 26, insert paragraph number - [56] Although the description above contains ...

Page 26, insert paragraph number - [57] Thus the scope of the invention should be ...